

## Ski trail grooming equipment type F-250

<b>Chassis</b>	
frames	steel - MIG welded
towing bar	removable - with pintle-hitch suitable to the Sherpa series
coating	anti-oxidation pre-coating plus epoxy powder-coating finish
<b>Grooming tool / first stage</b>	
type	mechanical
tool specifications	3 rows / spring mounted 112 hard-steel knives
grooming width	mm. 1.800
grooming depth	electro-actuated
comb	dual-stage finisher
combing width	mm. 2.500 incl. flaps
<b>Track-maker ( 1<sup>st</sup> unit as standard / 2<sup>nd</sup> unit on request)</b>	
tiller	12V DC electro-vibrating unit
max. rpm	3000 rpm
tool specifications	16 hardened-steel knives
grooming width	420 mm.
grooming depth	45 mm.
trackshoes	UHMW polyethylene with progressive compaction profile
trackshoes distance	mm. 220
base	Pro-glide hd-pe
track-maker width	540 mm.
additional side-plates	standard
track-maker lift-system	electro-actuated
track-maker pre-load	gas-spring
translator-system	mechanical
translator stroke	mm. 1.000
electric system	12 V DC
controls	remote computer with "can-bus" system
wheeling-system	standard

The machine meets the 2004/108 and 2006/42 EEC norms.